

# Excalibur Aventador S



**Case:** Skeletonized, Ø45 mm, C-SMC carbon with titanium container over molded with blue rubber, C-SMC carbon bezel with blue lacquered markings black DLC titanium crown over molded with rubber, Sapphire crystal with anti-reflective treatment and red metallization, titanium black DLC case back with sapphire crystal

**Thickness:** 13.3mm

**Calibre:** RD103SQ caliber, 90° V-shape double sprung balances linked with a differential. 5 patents related to this mechanism.

**Dial:** Skeleton dial with C-SMC carbon lower flange and black upper flange, rhodium plated indexes filled with white luminous SLN, 18K black PVD gold hands with red transfer and white luminous SLN tips

**Water resistance:** 5 BAR (50 m)

**Strap:** Interchangeable black rubber strap with blue Alcantara® inlay, red stitching

**Buckle:** Interchangeable and adjustable folding clasp. Titanium black DLC cover with titanium blades.

**Production:** 88 pieces

**Functions:** Hours, Minutes, jumping second, power reserve indicator

**Decorations:** Main plate and bridges circular-grained, shot-blasted and NAC coated.

**Number of parts:** 313 components

**Jewels:** 48

**Diameter:** 16''

**Thickness:** 7.8 mm

**Frequency:** 4 Hz (28'800 vph)

**Power-reserve:** 40 hours